

Detection and Identification: Fast, Accurate and Easy



RADEAGLE is a state-of-the-art handheld, radioisotope identification device (RIID) delivering superior speed and accuracy.

- Combining a large, high sensitivity crystal with an intelligent algorithm, the RADEAGLE can quickly, accurately, and simultaneously detect and identify four or more isotopes, typically in under 30 seconds, even in complex shielded or masked scenarios.
- ANSI 42.34 compliant, the RADEAGLE offers a user-friendly interface that is intuitive, simple to navigate, provides visually clarity, and utilizes an extensive array of alarms.
- Supports a variety of scintillation crystals including Nal(TI) and LaBr3(Ce) to optimize performance across multiple applications.
- Incorporating **decades of industry expertise** in detection and identification algorithms along with advanced hardware, electrical, and software systems, the **RADEAGLE is the handheld RIID of choice**.

Key Customers and Applications

- ✓ First Responders and Emergency Management
- Customs and Border Protection
- Security and Military Forces
- ✓ Nuclear Safeguards
- Environmental Management and Cleanup
- Nuclear Medicine and Scientific Institutes
- ✓ Scrap Steel and Recycling

Intelligent Algorithm – Unparalleled Speed and Accuracy

The RADEAGLE algorithm is unique, using a neuron ensemble to create a multi-agent system. This multiagent system in turn uses a mimetic learning algorithm that adapts reference data to the unique signature of the detector's sensors. While continuously measuring background radiation, this "neuro-spectroscopic brain," delivers unparalleled speed and accuracy for detecting and identifying over 67 nuclides, exceeding ANSI 42.34 requirements.



Operating Modes

The RADEAGLE uses five basic operating modes: Dose Rate, Detect, Easy-ID, Spectrum, and Advanced. These **five simple modes gives the user full system control** ranging from quick and accurate identification to extensive spectrum analysis to expert system configurations.





Application Centric Approach

A key benefit of the RADEAGLE algorithm is its optimization for multiple real-world applications. Through extensive simulation, validated and refined with real world empirical testing, the RADEAGLE's performance is tuned and optimized for key isotopes associated with SNM in the nuclear security and safeguards market, NORM and IND for environmental and industrial applications and MED for nuclear medicine. Underwater measurements are also supported with a submersible, Nal model.

Common Technical Specifications

RADIOLOGICAL PERFC	RMANCE				
Energy Range/MCA	11 keV to 3 MeV/2048 channels				
Calibration Source	Natural background. Optional embedded calibration source.				
Nuclide Library	 Am241, Ac228, Ag110m, Ba133, Ba140, Beta+, Bi207, Cd109, Cd115, Cd115m, Ce141, Cf2 Co57, Co58, Co60, Cr51, Cs134, Cs137, Eu152, Eu154, Eu155, Ga67, Ga68, I123, I125, I131, I132, In111, Ir192, Ir192s, K40, La140, Lu176, Lu177, Mn54, Mo99, Na22, Nb95, Nd14 Neutrons, Np237, Pd103, Pr144, Pu238, Ra226, RGPu, RGPuHS, Ru103, Sb12, Sb124, Se Sn113, Sr85, Sr90, Tc99m, Te132, Th232, Tl201, U232, U233, U235, U238, W181, WGPu, WGPuHS, Xe131m, Xe133, Xe133m, Xe135, Zr95 				
Nuclide Categories	Special nuclear material (SNM), Naturally occurring radiation (NORM), Industrial emitter (IND), or Medical source (MED)				
PHYSICAL					
Dimensions	248 mm x 115 mm x 152 mm (9.8" x 4.5" x 6.0")				
Display	640 x 480, 89 mm (3.5") Transflective Color TFT				
Batteries	Rechargeable AA NiMH battery pack, auxiliary battery case for AA NiMH or alkaline				
Operational Run Time	>8 hours with standard battery pack				
ENVIRONMENTAL					
Operating Temperature	-20°C to +50°C (-4°F to +122°F)				
Relative Humidity	10% – 90%, non-condensing				
Protection Rating	IP65, (3SGA models are IP68)				
COMPUTATIONAL					
Memory	>16 GB (1,000,000 spectra)				
CPU Speed	1 GHz				
File Formats	ANSI N42.42, SPE (IAEA)				
Connectivity	USB, WiFi, GPS (optional)				
SOFTWARE					
Operating System	Microsoft Windows (XP, Vista, 7, 8, 10), MAC OS X Yosemite, Linux (tested for Ubuntu)				

Model Specific Technical Specifications

Model	Detector Type	Detector Dimensions	PMT	GM	He3*	Resolution @ 662 keV ¹³⁷ Cs at ambient room temp	Sensitivity cps/µSv/h @ 662 keV ¹³⁷ Cs	Dose Rate Range Detector μSv/h	Dose Rate Range GM, up to Sv/h	Weight (grams)
RADEAGLE-3SG	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~		≤7.2%	>2500	0.01–200	1	~2620
RADEAGLE-3SG-H	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~	~	≤7.2%	>2500	0.01–200	1	~2720
RADEAGLE-3SGA	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~		≤7.2%	>2500	0.01–200	1	~2620
RADEAGLE-3SGA-H	Nal(TI)	76.2x25.4 mm (3x1 in)	3"	~	~	≤7.2%	>2500	0.01–200	1	~2720
RADEAGLE-2LG	LaBr3(Ce)	50.8x25.4 mm (2x1 in)	3"	~		≤3.0%	>1600	0.01–300	1	~2250
RADEAGLE-2LG-H	LaBr3(Ce)	50.8x25.4 mm (2x1 in)	3"	~	~	≤3.0%	>1600	0.01–300	1	~2550

*with internal moderator



RADEAGLE Radioisotope Identification Device

RADEAGLE AQUA

- IP 68
- Submersible to 15 meters
- Tested and proven ID algorithm with special modification to compensate for attenuation and scatter in water
- Floats in the water
- Rugged and durable for military use
- Bright yellow color for easy location in water
- Ideal for use in maritime environments immune to salt spray



It Floats!





RADEAGLE Radioisotope Identification Device

Ordering Information

Model	Description
RADEAGLE-3SG	Gamma Handheld RIID with 3x1 Nal(TI) detector and GM tube. Includes KCI calibration source, wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SG-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube and embedded calibration source. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SG-GPS	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube and GPS. Includes KCI calibration source, wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SG-GPS-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, GPS and embedded calibration source. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SG-H	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, and He-3 detector. Includes KCI calibration source, wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SG-H-ES	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, He-3 detector and embedded calibration source. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SG-H-GPS	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, He-3 detector and GPS. Includes KCI calibration source, wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SG-H-GPS-ES	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, He-3 detector GPS and embedded calibration source. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SGA	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube and AQUA option. Includes KCI calibration source, wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SGA-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option and embedded calibration source. Includes wall plug/ charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SGA-GPS	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option and GPS. Includes KCI calibration source, wall plug/ charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SGA-GPS-ES	Gamma Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option, GPS and embedded calibration source. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SGA-H	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option and He-3 detector. Includes KCI calibration source, wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SGA-H-ES	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option, He-3 detector and embedded calibration source. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-3SGA-H-GPS	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option, He-3 detector, and GPS. Includes KCI calibration source, wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case
RADEAGLE-3SGA-H-GPS-ES	Gamma/Neutron Handheld RIID with 3x1 Nal(TI) detector, GM tube, AQUA option, He-3 detector, GPS and embedded calibration source. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-2LG	Gamma Handheld RIID with 2x1 LaBr3(Ce) detector and GM tube. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-2LG-GPS	Gamma Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube and GPS. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-2LG-H	Gamma/Neutron Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube and He-3 detector. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.
RADEAGLE-2LG-H-GPS	Gamma/Neutron Handheld RIID with 2x1 LaBr3(Ce) detector, GM tube, He-3 detector and GPS. Includes wall plug/charger module, auto power adapter, spare AA battery pack, screwdriver, USB cable, and carry case.

Model	Description				
Accessories					
RE-AP009-1	Accu-Pack Smart Battery Pack with NiMH 7.2 V batteries				
RE-AP009-2	Accu-Pack Smart Battery Pack without batteries				
RE-CA019	Auto Power Adapter, 12 V				
RE-CC022	Carrying Case				
RE-CM020	Universal Wall Plug/Charger Module with 4 ft 11 in. (150 cm) cable. AC in: 100 V – 240 V; 620 mA; 50 Hz – 60 Hz. DC out: 12 V; 2.5 A.				
RE-HB021	Carrying Holster with Strap				

Ordering Information – continued



www.ortec-online.com

Tel. (865) 482-4411 ortec.info@ametek.com 801 South Illinois Avenue, Oak Ridge, TN 37830 U.S.A. Visit Our Website For International Office Locations Specifications subject to change 24-1211